



# HI-STRENGTH QUICK TO SET CONCRETE



**Drymix Hi-Strength Quick to Set Concrete is for the projects where structural strength to 36 MPa is required, i.e. steps, slabs, driveways, footings, corner posts or any job specified for strength up to 36 MPa.**

Ph: **0800 379 746** [www.drymix.co.nz](http://www.drymix.co.nz)

#### PRODUCT DESCRIPTION

**DRYMIX HI-STRENGTH QUICK TO SET** is an easy to use, fast-setting, high strength concrete consisting of a special blend of cement, graded dry quality sand and aggregates and selected additives. Only water is required.

**DRYMIX HI-STRENGTH QUICK TO SET** achieves a set in minutes and a 28 day strength of 36MPa.

**DRYMIX HI-STRENGTH QUICK TO SET** is ideal for applications involving placement of heavy posts, decks, retaining walls, foundations or footings, bollards, sun shade posts or any project requiring high strength concrete of up to 36 MPa. Simply concrete in the post and carry on with the job!

#### QUANTITIES

As a guide: For posts up to 1.8m in length, use one or two 25kg bags of **DRYMIX HI-STRENGTH QUICK TO SET**. For larger posts use two bags. Generally the diameter of a post hole should be twice the diameter of the post.

#### WATER

A measured, potable water supply is required.

#### SAFETY

As with all cement materials, avoid eye contact, swallowing and excessive skin contact.

- Freshly mixed concrete or mortar may cause skin irritation including alkaline burning and dermatitis.
- Avoid contact with the skin by wearing suitable clothing and gloves.
- In the event of contact with skin or eyes, rinse thoroughly with water.
- If swallowed, drink 1-2 glasses of water.
- If irritation persists, seek medical attention.



#### MIXING INSTRUCTIONS

##### 1. WET THE HOLE

Thoroughly wet the hole to compensate for any ground drainage which may soak up water required for the **DRYMIX HI-STRENGTH QUICK TO SET**. NB: In sandy soils line the post hole with plastic to slow water loss.

##### 2. PLACE

Place and position post in the hole.

##### 3. ADD WATER

Pour 2.5 to 3 litres of water per bag of **DRYMIX HI-STRENGTH QUICK TO SET** into the hole. When measuring allow for any ground water present.

##### 4. DRYMIX HI-STRENGTH QUICK TO SET

Immediately pour one bag of **DRYMIX HI-STRENGTH QUICK TO SET** evenly around the post – do not mix.

##### 5. CHECK

Re-check the post's positioning and sparingly add water to any dry **DRYMIX HI-STRENGTH QUICK TO SET** visible and level the surface straight away if necessary.

#### NOTE:

1. If using more than one bag of **DRYMIX HI-STRENGTH QUICK TO SET**, repeat steps 1-5.

2. After a minimum of 15 minutes, the hole can be topped up with compacted earth and the superstructure can be drilled or nailed, preferably with a nail gun as this creates less stress on the concrete.

#### STORAGE

Keep dry and store off the ground.

#### IMPORTANT

**Do not mix – pour directly into hole**

