



MORTAR BRICK MORTAR



Scan the QR code to visit our website.

PRODUCT DESCRIPTION

DRYMIX BRICK MORTAR is a grey easy-to-use, spreadable mortar mix designed for laying bricks in projects around the home. Perfect for building or repairing garden walls, letterboxes, edging, small retaining walls, or brick pillars. It takes the hassle out of mixing your own mortar from scratch as each bag is pre-mixed for consistent results – just add water and mix!

SUITABLE USES

- Garden walls
- Brick letterboxes
- Paver bedding
- Brick & block laying

KEY ADVANTAGES

- Smooth and spreadable: easy to trowel and shape for a neat finish.
- Reliable strength: premixed to achieve 12.5 MPA consistently.
- NZ compliant: meets NZS 4210: 2001.

MIXING INSTRUCTIONS

The BRICK MORTAR blend is designed for initial mixing with approximately 3L - 4.7L of water per 20kg bag. Providing that the mix is not made overly wet, the standard 28 day strength should be 12.5MPa in accordance with NZS 4210: 2001: Code of practice for masonry construction.

CONCRETE MIXER



1. Add water to your mixer.
2. Slowly pour in the full bag of DRYMIX BRICK MORTAR while mixing approximately 5 mins is sufficient.

WHEELBARROW



1. Add water to your wheelbarrow.
2. Gradually pour the bag and mix thoroughly until smooth. Do not over mix approximately 5 mins is sufficient.

TIPS

- Product should be applied at a layer depth of 10-13mm.
- Potlife of the mixture is 30-60mins, this will vary based upon the ambient conditions.
- Adjust water as needed based on seasonal and ambient conditions.
- Pointing is easier after mortar has initially set.

COVERAGE

Approximate coverage per 20kg bag: 20 bricks or 16 blocks.

PRODUCT LIMITATIONS

This product is used in unstructured applications. The more water is added in the mixture,

the weaker the mortar layer is formed. High speed agitation during the mixing may result in more air bubbles in the mortar mixture and a lower strength.

If your project requires Building Consent, please contact Dunlop Drymix at 0800 379 746 about the suitability of this product before use.

DRYING & CURING

Drying time depends on the climate. In general, allow for a minimum of 24 hours at 20°C.

STORAGE & SHELF LIFE

Store locked up. Keep dry and store off the ground. 12 months when stored in original unopened packaging.

COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS/Identification	Conc (%)
Silica crystalline - quartz	14808-60-7	>60%
Portland Cement	65997-15-1	20-40%
Silica, fumes	69012-64-2	<1%
Ingredients determined not to be harmful	Not Available	balanced

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

SAFETY DATA SHEETS ARE AVAILABLE AT WWW.DUNLOPDRYMIX.CO.NZ

Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand.

DANGER



DUST MASK



GLOVES



GOGGLES



CLOTHING



FOOTWEAR

HAZARD STATEMENTS

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Suspected of causing genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.



**SAFETY INSTRUCTIONS**

Do not breathe dust/fume. Use only outdoors or in a well ventilated area.
 Wear protective gloves, protective clothing, eye protection, face protection.
 Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood. Wash all exposed external body areas thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

RESPONSE

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF exposed or concerned:** Get medical advice/attention. Immediately call a POISON CENTER (0800 764 766)/ doctor/ physician/first aider. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

NOTE: MORTAR IS CONSIDERED IRRITATING TO THE SKIN UNDER THE CLASSIFICATION SYSTEM; HOWEVER, THERE IS A POSSIBILITY OF BURNS IF WET MORTAR OR CEMENT MIXTURES ARE LEFT IN CONTACT WITH THE SKIN FOR A PROLONGED TIME. MORTAR MAY CONTAIN SILICA (AS QUARTZ) IN TRACE AMOUNTS. 6.7A AND 6.9A APPLY IF QUARTZ SILICA IS PRESENT AS A FINE RESPIRABLE DUST.

DISPOSAL AND ENVIRONMENT

Mop up and collect recoverable excess material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill but check with your local council and only dispose of in accord with all regulations.

DO NOT ALLOW ANY OF THIS PRODUCT TO ENTER ANY DRAINS, SEWERS OR STORMWATER.

Do not allow any mortar waste, waste water or any fresh mortar wash off to go down any drains, sewers or stormwater as this is toxic to aquatic life such as fish or insects.

DISCLAIMER:

Please note: Recommendations for using this product are guidelines only. Dunlop Drymix Ltd provides no warranty, express or implied, regarding its suitability for specific uses, as product application is beyond our control. For advice on suitability, please contact Dunlop Drymix Ltd. If the product is defective, contact the merchant or Dunlop Drymix Ltd. For a refund or replacement, in accordance with the Consumer Guarantees Act. Dunlop Drymix Ltd is not liable for how the product is stored or used on-site as this is beyond our control.



This packaging is recyclable
(Polymethylene)

Last Updated on : March 2026

